

SPECIFICATIONS

Engine

Engine type Air cooled, 4-stroke, SOHC, 2-valve Displacement 249cc Bore & stroke 74.0×58.0mm

9.8:1 Compression ratio 20.8PS(15.3kW)/ 8000rpm Maximum horse power

20.1N·m(2.0kgf.m)/ 6000rpm

Fuel system Fuel injection Electric starter Starting system type Constant mesh. 5-speed Transmission type Clutch type Wet, multiple-disc

Chassis

Maximum torque

Diamond Frame type

100/80-17M/C 52P - Tubeless Tyre size (Front) 140/70-17M/C 66S - Tubeless Tyre size (Rear) Brake type (Front) Disc Brake (282mm)

Disk Brake (220mm) Brake type (Rear) Suspension type (front/rear) Telescopic fork/ 7-Step Adjustable

Monocross Suspension

41.0 mm Inner tube

(diameter of front fork)

Dimensions

Overall L x W x H (FZS 25) 2.015 mm x 820 mm x 1.105 mm 2.015 mm x 775 mm x 1.075 mm Overall L x W x H (FZ 25) Seat height 795mm Wheelbase 1360mm Minimum ground clearance 160mm Weight (FZS 25) 154kg (with oil & a full fuel tank) Weight (FZ 25) 153kg (with oil & a full fuel tank)

2.5m

14 L

Other Information

Minimum turning radius

Fuel tank capacity

Battery 12V, 6.0Ah Headlight LED LED Daytime Running Light LED Brake/ Tail light Digital Speedometer Tachometer Fuel gauge Digital Fuel consumption indicator Equipped Clock Digital Side stand engine cut off switch Equipped ABS Dual channel ABS















"The specifications and design of the motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colours shown may not match the actual colour due to printing limitations. *Conditions Apply. **Warranty Extended for Engine, FI System, AIS System and Electrical including Wiring harness. 5 years warranty is applicable only in case of purchase of Yamaha protection plus policy during validity period, please refer the protection plus policy for details."

Yamaha Motor India Sales Pvt. Ltd, AKDR Tower - 5th Floor, Door No, 3/381, Rajiv Gandhi Salai (OMR), Mettukuppam, Chennai - 600 097 Phone: 044-3814 7000, Toll Free No.: 1800 420 1600, Email: info@yamaha-motor-india.com, www.yamaha-motor-india.com



Long Visor*

A stylish crown to the front face, it helps minimize wind blast when you are tearing down the highway.



EVERYTHING YOU DESIRE IN A **250CC** BIKE TO PUSH THE LIMITS



249cc, 4 Stroke Single-cylinder BS 6 Engine

Based on a reliable engine proven on sport bikes for the Japanese market, this engine is fine tuned and optimized for Indian conditions and is BS 6 compliant.



Brush Guard*

Whatever terrain you charge into, your grip remains firm and your hands are protected.



Golden Colour Wheel*

Adds a touch of drama to your street presence. Stand out on every street you ride on!



Multi Function Negative LCD Instrument Cluster

Readable even at the darkest hour and loaded with useful information like Trip Meter, Check Engine Indicator and real time mileage.



Bi-Functional LED Headlight with LED Daytime Running Lamp



Be more visible & enjoy enhanced night vision.



Makes easier to control while enhancing economy at the same time.

Weight for FZ 25 is 153 kg & for FZS 25 it is 154 kg



For over a decade, the FZ series has rightfully retained the title of the lord of the streets. Inspiring riders from across the country who look for not just a good looking bike but a presence, a reflection of their macho character, and lots of exhilaration. Twelve years later,

the iconic Yamaha FZ is geared up to push the limits even further. To take you through the urban jungle and beyond. Because it believes that adventures don't have to be big to be unforgettable. What matters is you experience them, every day.



Side Stand Engine Cut-off Switch

Added safety – engine cuts off if the stand is not retracted.

*These features are available in FZS 25